



F-350/F-450/F-550 SUPER DUTY® CHASSIS CABS

CONVENTIONAL TOWING⁽¹⁾⁽²⁾

Trailer weights shown assume 1,000 lbs. second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed listed GCWR.

		Maximum Loaded Trailer Weight (Lbs.) – Automatic Transmission																								
		REGULAR CHASSIS CAB								SUPER CHASSIS CAB								CREW CHASSIS CAB								
		F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW	F-450 4x4 DRW	F-550 4x2 DRW	F-550 4x4 DRW	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW	F-450 4x4 DRW	F-550 4x2 DRW	F-550 4x4 DRW	F-350 4x2 SRW	F-350 4x4 SRW	F-350 4x2 DRW	F-350 4x4 DRW	F-450 4x2 DRW	F-450 4x4 DRW	F-550 4x2 DRW	F-550 4x4 DRW	
6.2L SOHC V8	3.73	19,000	12,300	11,800	-	-	-	-	-	-	12,000	11,500	-	-	-	-	-	-	11,700	11,300	-	-	-	-	-	-
		19,500	-	-	13,300	11,800	-	-	-	-	-	-	12,000	11,500	-	-	-	-	-	-	11,700	11,300	-	-	-	-
FFV	4.30	22,000	12,500	12,500	-	-	-	-	-	-	12,500	12,500	-	-	-	-	-	-	12,500	12,500	-	-	-	-	-	-
		22,500	-	-	15,000	14,800	-	-	-	-	-	-	15,000	14,500	-	-	-	-	-	-	14,700	14,300	-	-	-	-
6.8L SOHC V10	4.88	26,000	-	-	-	16,000	16,000	16,000	16,000	-	-	-	-	16,000	16,000	16,000	16,000	-	-	-	-	16,000	16,000	16,000	16,000	-
6.7L V8 Turbo	3.73	23,500	12,500	12,500	-	-	-	-	-	12,500	12,500	-	-	-	-	-	-	-	12,500	12,500	-	-	-	-	-	-
		24,500	-	-	15,000	15,000	-	-	-	-	-	-	15,000	15,000	-	-	-	-	-	-	15,000	15,000	-	-	-	-
6.7L V8 Diesel	4.10	24,500	-	-	15,000	15,000	-	-	-	-	-	-	15,000	15,000	-	-	-	-	-	-	15,000	15,000	-	-	-	-
		26,000	-	-	-	16,000	16,000	16,000	16,000	-	-	-	-	16,000	16,000	16,000	16,000	-	-	-	-	16,000	16,000	16,000	16,000	-
	4.30	30,000(3)	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	-	-	-
		35,000(3)	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	
	4.88	26,000	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	
		35,000(3)	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	-	-	-	-	-	-	16,000	16,000	

5th-WHEEL TOWING

6.2L SOHC V8	3.73	19,000	12,300	11,800	-	-	-	-	-	12,000	11,500	-	-	-	-	-	-	-	11,700	11,300	-	-	-	-	-	-
		19,500	-	-	13,300	11,800	-	-	-	-	-	12,000	11,500	-	-	-	-	-	-	-	11,700	11,300	-	-	-	-
FFV	4.30	22,000	15,300	14,800	-	-	-	-	-	15,000	14,500	-	-	-	-	-	-	-	14,700	14,200	-	-	-	-	-	-
		22,500	-	-	16,300	14,800	-	-	-	-	-	15,000	14,500	-	-	-	-	-	-	-	14,700	14,300	-	-	-	-
6.8L SOHC V10	4.88	26,000	-	-	-	18,300	17,900	18,200	17,900	-	-	-	-	17,800	17,400	17,800	17,400	-	-	-	-	17,600	17,200	17,600	17,200	-
6.7L V8 Turbo	3.73	23,500	16,000	15,500	-	-	-	-	-	15,500	15,000	-	-	-	-	-	-	-	15,300	14,800	-	-	-	-	-	-
		24,500	-	-	16,500	16,100	-	-	-	-	-	16,200	15,600	-	-	-	-	-	-	-	15,900	15,500	-	-	-	-
6.7L V8 Diesel	4.10	24,500	-	-	16,500	16,100	-	-	-	-	-	16,200	15,600	-	-	-	-	-	-	-	15,900	15,500	-	-	-	-
		26,000	-	-	-	17,400	17,000	17,400	17,000	-	-	-	-	17,000	16,600	17,000	16,600	-	-	-	-	16,800	16,300	16,800	16,300	-
	4.30	30,000(3)	-	-	-	21,400	21,000	-	-	-	-	-	-	21,000	20,600	-	-	-	-	-	-	20,800	20,300	-	-	-
		35,000(3)	-	-	-	-	-	26,400	26,000	-	-	-	-	-	-	26,000	25,600	-	-	-	-	-	-	25,800	25,300	
	4.88	26,000	-	-	-	-	-	17,200	16,900	-	-	-	-	-	-	16,800	16,500	-	-	-	-	-	-	16,600	16,300	
		35,000(3)	-	-	-	-	-	26,200	25,900	-	-	-	-	-	-	25,800	25,500	-	-	-	-	-	-	25,600	25,300	

(1) Maximum loaded trailer weight requires weight distribution hitch. See page 29 for additional information.

(2) Super Duty Chassis Cab does not offer a conventional hitch receiver as a factory-installed option. (3) Available with High-Capacity Trailer Tow Package only.

Note: Trailer tongue (trailer king pin for 5th-wheel towing) load weight should be 10-15% (15-25% for 5th-wheel towing) of total loaded trailer weight. Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo added to towing vehicle. Addition of trailer tongue (trailer king pin for 5th-wheel towing) load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.