



E-Series

E-SERIES VAN/WAGON (1)

Engine	Axle Ratio	GCWR (Lbs.)	Maximum Loaded Trailer Weight (Lbs.) – Automatic Transmission										
			VAN						WAGON				
			E-150	E-150 Extended	E-250	E-250 Extended	E-350 Super Duty	E-350 Super Duty Extended	E-350 Super Duty	E-350 Super Duty Extended 11-Pass.	E-350 Super Duty Extended 14-/15-Pass.		
4.6L SOHC V8	3.73	11,500	6,000	5,900	6,000	5,900	–	–	5,600	–	–	–	
	4.10	12,000	6,500	6,400	6,500	6,400	–	–	6,100	–	–	–	
5.4L SOHC V8	3.73	13,000	7,500	7,300	7,400	7,300	7,400	7,200	7,000	6,700	6,500	6,300	
	4.10	13,000	7,500	7,300	7,400	7,300	7,400	7,200	7,000	6,700	6,500	6,300	
6.8L SOHC V10	3.73	15,000	–	–	–	–	–	9,100	9,000	–	8,500	8,300	8,100
	4.10	18,500	–	–	–	–	–	10,000	10,000	–	10,000	10,000	10,000

(1) Maximum loaded trailer weight requires weight-distributing hitch. See page 27 for additional information.

Note: Trailer tongue load weight should be 10-15% of total loaded trailer weight. Make sure vehicle payload (reduced by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle. Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.



E-SERIES CUTAWAY & STRIPPED CHASSIS

To determine Maximum Trailer Weight, subtract your vehicle's GVWR from the following GCWRs:

- **E-250 Super Duty Cutaway GCWR:**
– 4.6L V8/4R75E – 12,000 lbs.
- **E-350 Super Duty Cutaway GCWRs:**
– 5.4L V8/4R75E – 9,600 lbs. (SRW)
– 5.4L V8/4R75E – 10,050 lbs. (DRW)
– 5.4L V8/5R110W – 13,000 lbs.
– 6.8L V10/5R110W – 18,500 lbs.
- **E-350 Super Duty Extended Cutaway GCWR:**
– 5.4L V8/4R75E – 10,600 lbs.
- **E-450 Super Duty Cutaway GCWRs:**
– 5.4L V8/5R110W – 14,050 lbs.
– 6.8L V10/5R110W – 22,000 lbs.
- **E-350 Super Duty Stripped Chassis GCWRs:**
– 5.4L V8/5R110W – 13,000 lbs.
– 6.8L V10/5R110W – 18,500 lbs.
- **E-450 Super Duty Stripped Chassis GCWRs:**
– 5.4L V8/5R110W – 14,050 lbs.
– 6.8L V10/5R110W – 22,000 lbs.