2022 FORD BRONCO TWO- AND FOUR-DOOR MODEL

TECHNICAL SPECIFICATIONS




BODY

Vehicle typeMidsize two-door and four-door rugged 4x4 SUVTrim seriesBase, Big Bend™, Black Diamond™, Outer Banks™, Badlands™, Wildtrak™Option packagesMid, High, Lux, Sasquatch™ PackageFinal assembly locationMichigan Assembly Plant, Wayne, Michigan

ENGINES

	2.3-liter EcoBoost®	2.7-liter EcoBoost		
Configuration	Ti-VCT GTDI I-4	Ti-VCT GTDI 60-degree V6		
Displacement	138 cu. in. (2,264 cc)	164 cu. in. (2,694 cc)		
Bore x stroke	3.45 in. x 3.7 in. (87.55 mm x 94 mm)	3.27 in. x 3.27 in. (83 mm x 83 mm)		
Compression ratio	10.0:1	10.0:1		
Fuel delivery	Direct injection	Port fuel/direct injection		
Engine control system	Chassis integrated powertrain control module	Chassis integrated powertrain control module		
Engine block material	High-pressure die cast aluminum alloy	Compacted graphite iron		
Pistons	Lightweight, high-strength cast aluminum with low-friction skirt coating and steel ring	Lightweight, high-strength cast aluminum with low-friction skirt coating and steel ring		
Connecting rods	Forged steel	Forged steel		
Crankshaft	Forged steel	Forged steel		
Valve diameter/lift	Intake, 32.5 mm/8.9 mm Exhaust, 30 mm/7.8 mm	Intake, 32.50 mm/10 mm Exhaust, 28.30 mm/9.0 mm		
Valve lifters	Direct acting mechanical bucket	Roller finger follower, hydraulic compensating lash adjusters		
Intake	Composite, split plenum	Composite		
Ignition	Coil on plug	Coil on plug		
Induction	Twin-scroll turbocharger with electrically actuated wastegate	Dual mono-scroll turbochargers with electrically actuated wastegate		
Exhaust	Cast iron	Integrated cylinder head casting		
Recommended fuel	Regular unleaded 87 octane minimum	Regular unleaded 87 octane minimum		
Oil capacity	6.2 quarts	7.0 quarts		
Coolant capacity	11.1 liters	11.7 liters		
Exhaust system	Single catalyst with resonator and single muffler	Double catalyst with resonator and single muffler		
Alternator	Standard: Single 240A	Standard: Single 240A		
Battery group	H7 AGM 80 AH 800 CCA	H7 AGM 80 AH 800 CCA		
SAE horsepower (regular fuel)	275 @ 5,700 rpm	315 @ 5,500 rpm		
SAE torque (regular fuel)	315 @ 3,400 rpm	410 @ 3,250 rpm		
SAE horsepower (premium fuel)*	300 @ 5,700 rpm	330 @ 5,250 rpm		
SAE torque (premium fuel)*	325 @ 3,400 rpm	415 @ 3,100 rpm		
Build location	Cleveland Engine Plant	Lima Engine Plant		





DRIVETRAIN						
Layout	Longitudinally mounted front engine with center-mounted transfer case, independent front axles/solid rear axles					
TRANSMISSIONS						
Standard	7-speed (6+1 cra	wler gear) Getrag manual (offered on 2.3-lite	er engine only)			
Optional	10-speed autom	natic (available on both 2.3- and 2.7-liter engi	ines)			
	7-Speed Manual 10-Speed Automatic					
	Crawler	Crawler 6.588:1		4.714:1		
	First	4.283:1	Second	2.997:1		
	Second	2.365:1	Third	2.149:1		
	Third	1.453:1	Fourth	1.769:1		
Gear Ratios	Fourth	1.000:1	Fifth	1.521:1		
	Fifth	0.776:1	Sixth	1.275:1		
	Sixth	0.646:1	Seventh	1.000:1		
	Reverse	-5.625:1	Eight	0.853:1		
			Ninth	0.689:1		
			Tenth	0.636:1		
			Reverse	-4.885:1		
Transfer Cases	Standard		Optional			
		ime engagement electronic v, 2.72:1 low ratio	Advanced 4x4 v engagement, 3.	vith 4A mode automatic on-demand .06:1 low ratio		
Maximum crawl ratios*		d manual with standard ESOF ed speed automatic with standard ESOF	94.75:1 – 7-speed manual with optional Advanced 4x4 67.80:1 – 10-speed automatic with optional Advanced 4x4			
Flat-tow capability	Yes		Yes			
Axles	Front	Front				
Standard		K [®] M190 independent front suspension	Dana 44™ Adva	nTEK M220 solid rear differential		
Optional		:K® M210 independent front suspension rforma-TraK electronic locker		nTEK M220 solid rear differential rforma-TraK electronic locker		
CHASSIS						
Туре		; fully boxed high-strength steel frame with s ISS) System with low-mass independent froi er springs				
Suspensions	Front		Rear			
Standard		y A-arms with long-travel coil-over springs, avy-duty dampers	220 mm solid rear axle with long-travel, variable rate coilover springs, HOSS-tuned heavy-duty dampers			
Optional	Bilstein® positio end-stop contro	n-sensitive dampers with ol valves	Bilstein position-sensitive dampers with end-stop control valves			
Off-road capability	Two-door		Four-door			
Ground clearance	8.4/11.6		8.3/11.5 (Base/35-inch tires)			
Suspension travel front/rear (millimeters)	202/249 (Base) 222/259 (Badla		202/249 (Base) 222/259 (Badlands)			
Approach angle (degrees)	35.5/43.2 (Base	/35-inch tires)	35.5/43.2 (Base/35-inch tires)			
Breakover angle (degrees)	21.1/29.0 (Base/	'35-inch tires)	20.0/26.3 (Base	e/35-inch tires)		
Departure angle (degrees)	29.8/37.2 (Base	/35-inch tires)	29.7/37.0 (Base/35-inch tires)			
Ramp travel index (Badlands only) (Stabilizer Bar connected and disconnected)	560/700 (proje	cted)	500/620 (projected)			
Maximum water fording (inches) (Based on Sasquatch package)	33.5		33.5			



STEERING

	Two-door	Four-door	
Туре	Three-mode rack-and-pinion steering with standard, comfort and sport modes controlled via Terrain Management System™ with G.O.A.T. Modes™ (Goes Over Any Type of Terrain)		
Turning radius (curb-to-curb)	35.53 feet (10.83 m)	12.13 m (Badlands)/12.15 m (Sasquatch)	

BRAKES

	Front	Rear
Туре	Four-wheel power disc brakes with four-sensor, four-channe	l antilock braking system and electronic stability control
Boost	2.3-liter engine, vacuum brake boost, 2.7-liter engine, electro	nic brake boost
Brake configuration	Vented discs, twin-piston floating caliper	Discs with single-piston floating caliper, integral electronic parking brake
Rotor diameter/thickness	311 mm x 34 mm	308 mm x 24 mm
Pad material	Non-asbestos organic	Non-asbestos organic
Calipertype	Twin 51-mm floating	Single 54-mm floating
Pad swept area	413 cm ²	373 cm ²

BODY

	Two-door	Four-door		
Tops standard (varies by trim series)	Removable hardtop	Removable soft-top Removable hardtop		
Roof panel weight (pounds)	14.0 front left, 15.4 front right	13.6 front left, 14.5 front right, 28.1 mid panel		
Doors/storage	Two removeable frameless doors	Four removable frameless doors Available rear storage for four doors		
Door weight (pounds)	Front 62	Front 55/Rear 44		
Modular section	Doors, roof panels, front fenders, grille, fender flares, rear qu	arter panels, bumpers		
Rock rail	Standard on Black Diamond and Badlands series dealer installed accessory on all other Bronco series			
Tube steps	Standard on Outer Banks, available on Big Bend and Wildtrak			
Underbody protection	Black Diamond, Widltrak (optional): Five steel underbody shields including engine shield, transfer case shield, fuel tank shield, shin guards and heavy-duty front bash plate* Badlands: Six steel underbody shields including engine shield, transfer case shield, fuel tank shield, shin guards, stabilizer-bar shield and heavy-duty front bash plate*			
Modular bumpers	Heavy-duty powder-coated modular steel front bumper with heavy-duty bash plate standard on Black Diamond and Badlands, available on all other series			
Washout vinyl flooring with drain plugs	Standard on Black Diamond and Badlands series			
Trail sights with 150-pound tie-down capacity	Standard on all Bronco series			



TECHNOLOGY

	Standard modes, Base (5): Normal, Eco, Sport, Slippery and Sand
	Big Bend, Outer Banks (6): Normal, Eco, Sport, Slippery, Mud/Ruts and Sand
Terrain Management with G.O.A.T. Modes	Black Diamond (7): Normal, Eco, Sport, Slippery, Mud/Ruts, Sand and Rock Crawl
	Badlands, First Edition (7): Normal, Eco, Slippery, Mud/Ruts, Baja, Sand and Rock Crawl
	Wildtrak (7): Normal, Eco, Sport, Slippery, Baja, Mud/Ruts and Sand
Trail control Standard on all Bronco series with 10-speed automatic transmission	
Trail turn assist Standard on all Bronco series with 10-speed automatic transmission	
Trail one-pedal drive	Standard on 2.7-liter V6 models with 10-speed automatic transmission

	Base	Big Bend	Black Diamond	Outer Banks	Badlands	Wildtrak
HMI/audio system, SYNC® 4 system standard	8-inch	8-inch	8-inch	8-inch	8-inch	8-inch
HMI/audio system, SYNC 4 system requires optional high package	N/A	N/A	N/A	12-inch	12-inch	12-inch
SYNC 4 System with Connected Built-in Navigation	N/A	0	0	0	0	0
360-degree camera system	N/A	N/A	N/A	0	0	0
B&O sound system® with 10 speakers (Optional with Lux Package)	N/A	N/A	N/A	0	0	0
Ford Co-Pilot360™ Technology						
Includes: - Auto high beam headlamps - Pre-Collision Assist with automatic emergency braking includes: - Pedestrian detection - Forward collision warning - Dynamic brake support - Hill Descent Control** (manual transmission only) - Hill start assist - Rearview camera with backup assist grid	S	S	S	S	S	S
Mid Package — Ford Co-Pilot360 includes: - Auto high beamheadlamps - Blind Spot Information System with cross-traffic alert - Pre-Collision Assist with Automatic Emergency Braking - Lane-Keeping Systemincludes: - Lane-keeping alert - Lane-keeping assist - Driver alert - Rearview camera with backup assist grid lines Plus, Ford Co-Pilot360 technologies	N/A	0	0	S	0	S
High Package — includes Base/Mid Package content includes: -360-degreecamera -Forward sensing system Plus, Ford Co-Pilot360 technologies	N/A	N/A	N/A	0	0	0
Lux Package – includes Base/Mid/ High Package content includes: - Adaptive cruise control - Evasive steering assist Plus, Ford Co-Pilot360 technologies	N/A	N/A	N/A	0	0	0

SAFETY/CONTROL SYSTEMS

ABS/stability control	AdvanceTrac® with Roll Stability Control® electronic stability control standard on all models, trailer sway control, electric power-assisted steering, and ABS			
Airbags	First-row driver and passenger dual-stage front and seat side airbags All rows: Safety Canopy side-curtain airbags with rollover sensors for all rows			



LIGHTING/CONVENIENCE

	Base	Big Bend	Black Diamond	Outer Banks	Badlands	Wildtrak
Headlamps Auto on/off LED Auto high-beam	S	S	S	S	S	S
Bronco signature LED lighting	N/A	0	N/A	S	S	S
LED fog lamps	N/A	S	S	S	S	S
Mirror LED approach lamps and LED spotlights	N/A	N/A	N/A	0	0	0
Overhead upfitter switches with six-pre-wired user-defined electrical connections	0	0	S	0	S	S
Dual-control HVAC automatic temperature control1	N/A	0	0	S	0	S
Heated seats	N/A	0	0	S	0	S
Central locking system with keyless entry and push-button start	S	S	S	S	S	S
Push button start	S	S	S	S	S	S
Intelligent access (lock/unlock)	N/A	0	0	S	0	S
Remote start system with FordPass Connect (automatic transmission models only)	S	S	S	S	S	S
Power window	S	S	S	S	S	S

Accessory Electrical

One 110V AC 400 watt power outlet (Mid Package and up; rear of center console)

Power points (12V) – one (1) center floor console, one (1) cargo area

Standard: Smart Charging Multimedia USB Ports, First Row – One (1) USB-A and one (1) USB-C; Smart Charging USB Ports, Second Row – One (1) USB-A and one (1) USB-C in the back side of the center floor console

Optional: Lux package – Smart Charging USB Ports, dash board – One (1) USB-A and one (1) USB-C

WHEELS	Series	
Standard	Base	16-inch bright polished silver-painted steel
Standard	Big Bend	17-inch Carbonized Gray-painted aluminum
Standard	Black Diamond	17-inch black gloss-painted black steel
Optional	Black Diamond	17-inch black mid-gloss-painted aluminum
Standard	Outer Banks	18-inch bright machined black high-gloss-painted aluminum
Standard	Badlands	17-inch machined Carbonized Gray-painted aluminum
Optional	Badlands	17-inch black high-gloss-painted aluminum with Carbonized Gray beauty ring, beadlock-capable
Standard	Wildtrak*	17-inch black high-gloss-painted aluminum with black beauty ring, beadlock-capable
Sasquatch Package	Series	
Optional	Base, Big Bend, Black Diamond, Badlands	17-inch black high-gloss-painted aluminum with warm alloy beauty ring, beadlock-capable

TIRES (Inches)							
Diameter	30	32	32	32	33	33	35
Width	255/70R16	255/75R17	255/70R18	265/70R17	285/70R17	285/70R17	315/70R17
Wheel size	16x7	17x7.5	18x7.5	17x7.5	17x8	17x8	17x8.5
Tread type	A/S	A/T	A/T	A/T	A/T	M/T	M/T
Supplier	Bridgestone	Bridgestone	Bridgestone	General Tire	BFGoodrich	Goodyear	Goodyear
Brand	Dueler H/T 685	Dueler A/T RH-S	Dueler A/T RH-S	General Grabber A/Tx	All-Terrain TA KO2	Territory	Territory
Series	Base	Big Bend	Outer Banks	Black Diamond	Badlands	Badlands Optional	Sasquatch Wildtrak



DIMENSIONS/CAPACITIES (Inches)

DIMENSIONS/CAPACITIES (Inches)	T	
Miles III	Two-door	Four-door
Wheelbase	100 /	116.1
All series	100.4	116.1
Length		
Base	173.7	189.4
Big Bend	173.7	189.4
Wildtrak	173.7	189.5
Badlands	174.8	190.5
Height		
Base	71.9	73.0 (soft-top)
Big Bend	72.9	72.9
Wildtrak	75.2	75.3
Badlands (When available roof racks are installed, add 3.6 inches to two-door models, 3.4 inches to four-door models for maximum height)	73.8	73.9
Width (with mirrors folded)		
Base/Big Bend	75.9	75.9
Wildtrak	79.3	79.3
Badlands	76.3	76.3
Track width, front/rear		
Base/Big Bend/Badlands	65.0/65.0	65.0/65.0
Wildtrak	66.9/66.9	66.9/66.9
Seating capacity	Four	Five
Passenger volume, hardtop (cu. ft.)	99	103.7
Passenger volume, soft-top (cu. ft.)	N/A	108.2
Behind first row, hardtop (cu. ft.)	52.3	77.6
Behind first row, soft-top (cu. ft.)	N/A	83.0
Behind second row, hardtop (cu. ft.)	22.4	35.6
Behind second row, soft-top (cu. ft.)	N/A	38.3
Headroom		
First row, hardtop	41.0	40.8
First row, soft-top	N/A	43.3
Second row, hardtop	39.8	40.1
Second row, soft-top	N/A	41.1
Legroom		
First row	43.1	43.1
Second row	35.7	36.3
Hiproom		
First row	56.3	55.9
Second row Second row	43.3	54.8
Shoulderroom		
First row	57.1	57.1
Second row Second row	51.8	56.5
Fuel capacity (gallons)		
	16.9	20.8



OPTION GROUP HIGHLIGHTS

Mid Package equipmentSYNC 4 with 8-inch LCD touch screen/audio system, connected navigation, dual-zone HVAC, front-row heated seats, two-group highlightsdoor intelligent access, remote start system,* Ford Co-Pilot360, reverse sensing system, rear passenger power outlet

High Package equipment Includes all Mid Package content plus:

group highlights

SYNC 4 with 12-inch LCD touch screen/audio system and information on-demand panel, 360-degree camera, forward sensing system, additional sound deadening, mirror-mounted LED approach lamps and spotlights

Includes all Mid and High Package content plus:


Lux Package equipment group highlights

10-speaker B&O Sound System by Bang & Olufsen, adaptive cruise control and evasive steering assist, heated steering wheel, connected built-in navigation with three years of service, wireless charging pad and dash-mounted USB-A and

USB-C smart charging ports

MAXIMUM CONVENTIONAL TOWING CAPABILITIES

			Vehicle weight (lbs.)			Weight ratings (lbs.)					
		Base curb weight		Payload (without	Ratings			Trailer tow**	Maximum GCWR		
					options)	GVWR	GA	WR	1011	ocm.	
Two-Door†			Front	Total	Total	Total	Front	Rear	Maximum	Total	
Trim	Engine	Transmission									
Base	2.3-liter EcoBoost I-4	7-speed manual	2,338	4,294	1,246	5,540	2,900	3,000	3,500 [†]	8,780	
Big Bend	2.3-liter EcoBoost I-4	7-speed manual	2,344	4,304	1,236	5,540	2,900	3,000	3,500	8,780	
Black Diamond	2.3-liter EcoBoost I-4	7-speed manual	2,490	4,587	1,053	5,640	2,900	3,000	3,500	8,780	
Badlands	2.3-liter EcoBoost I-4	7-speed manual	2,576	4,699	1,021	5,720	2,900	3,000	3,500	8,780	
Base	2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,353	4,314	1,226	5,540	2,900	3,000	3,500 [†]	8,480	
Big Bend	2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,359	4,324	1,216	5,540	2,900	3,000	3,500	8,780	
Black Diamond	2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,504	4,605	1,034	5,640	2,900	3,000	3,500	8,480	
Outer Banks	2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,402	4,413	1,127	5,540	2,900	3,000	3,500	8,480	
Badlands	2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,591	4,719	1,001	5,720	3,000	3,000	3,500	8,780	
Base	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,493	4,466	1,234	5,700	3,000	3,000	3,500 [†]	8,740	
Big Bend	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,499	4,476	1,224	5,700	3,000	3,000	3,500	8,740	
Black Diamond	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,644	4,757	1,022	5,780	3,000	3,000	3,500	8,840	
Outer Banks	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,542	4,565	1,135	5,700	3,000	3,000	3,500	8,740	
Badlands	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,731	4,871	989	5,860	3,000	3,000	3,500	8,840	
Wildtrak	2.7-liter EcoBoost V6	10-speed selectshift automatic	2,544	4,574	1,069	5,740	3,000	3,000	3,500	8,740	





MAXIMUM CONVENTIONAL TOWING CAPABILITIES (CONTINUED)

	,	Veh	icle Weight (lbs.)	Weight Ratings (lbs.)					
		Base curb weight		Payload (without	Ratings			Trailer	Maximum GCWR	
				options)	GVWR	GAWR		tow	COTTI	
		Front	Total	Total	Total	Front	Rear	Maximum	Total	
Engine	Transmission									
2.3-liter EcoBoost I-4	7-speed manual	2,477	4,466	1,454	5,920	3,090	3,070	3,500	8,780	
2.3-liter EcoBoost I-4	7-speed manual	2,671	4,823	1,196	6,020	3,170	3,070	3,500	8,780	
2.3-liter EcoBoost I-4	7-speed manual	2,757	4,937	1,162	6,100	3,170	3,070	3,340	8,780	
2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,492	4,476	1,444	5,920	3,090	3,070	3,500 [†]	8,480	
2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,497	4,486	1,434	5,920	3,090	3,070	3,500	8,480	
2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,691	4,843	1,196	6,040	3,170	3,070	3,500	8,780	
2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,543	4,577	1,343	5,920	3,090	3,070	3,440	8,480	
2.3-liter EcoBoost I-4	10-speed selectshift automatic	2,777	4,957	1,162	6,120	3,170	3,070	3,320	8,780	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,622	4,628	1,432	6,060	3,220	3,070	3,500 [†]	8,740	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,627	4,638	1,422	6,060	3,220	3,070	3,500	8,740	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,821	4,995	1,124	6,120	3,270	3,070	3,500	8,840	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,673	4,729	1,331	6,060	3,220	3,070	3,500	8,740	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,907	5,109	1,070	6,180	3,270	3,070	3,320	8,840	
2.7-liter EcoBoost V6	10-speed selectshift automatic	2,680	4,757	1,322	6,080	3,220	3,070	3,460	8,840	
ITY										
Bumper-to-bumper Three years/36,000 miles										
osion Five years/unlimited miles dside assistance 24-hour/day (3 years/36 miles)										
	2.3-liter EcoBoost I-4 2.7-liter EcoBoost V6	2.3-liter EcoBoost I-4 2.7-liter EcoBoost V6	Engine Transmission 2.3-liter EcoBoost I-4 7-speed manual 2,477 2.3-liter EcoBoost I-4 7-speed manual 2,671 2.3-liter EcoBoost I-4 7-speed manual 2,757 2.3-liter EcoBoost I-4 10-speed selectshift automatic 2,492 2.3-liter EcoBoost I-4 10-speed selectshift automatic 2,3-liter EcoBoost I-4 10-speed selectshift automatic 2,691 2.3-liter 10-speed selectshift automatic 2,543 2.3-liter 10-speed selectshift automatic 2,543 2.3-liter 10-speed selectshift automatic 2,777 2.3-liter 10-speed selectshift automatic 2,777 2.7-liter 10-speed selectshift automatic 2,777 2.7-liter 10-speed selectshift automatic 2,622 2.7-liter 10-speed selectshift automatic 2,627 2.7-liter 10-speed selectshift automatic 2,627 2.7-liter 10-speed selectshift automatic 2,821 2.7-liter 10-speed selectshift automatic 2,673 2.7-liter 10-speed selectshift automatic 2,673 2.7-liter Selectshift automatic 2,673 2.7-liter Selectshift automatic 2,680 2.7-liter Selectshift automatic 2,680 2.7-liter Selectshift automatic 2,680 2.7-liter Selectshift automatic 2,680	Base curb weight Front Total	Base curber Weight Weigh	Base curbery billions Payload without options Govwr	Base curb Base	Payload Payl	Payload (without options) Payload (without options)	

