



2026 T-250 Cargo Van Medium Roof in extra-cost color Ingot silver Metallic

Transit®

PASSENGER VAN

			CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹							
			REAR-WHEEL DRIVE				ALL-WHEEL DRIVE			
Automatic Transmission			350	350	350	350	350	350	350	350
Engine	Axle Ratio	GCWR (lbs.)	148" WB Low Roof	148" WB Medium Roof	148" WB High Roof	148" WB Extended High Roof	148" WB Low Roof	148" WB Medium Roof	148" WB High Roof	148" WB Extended High Roof
3.5L PFDI V6	3.73	10,800	4,200	4,100/4,000 ²	3,900		4,000	3,800 ²	3,700	
	4.10	11,200	4,500	4,400/4,300 ²	4,200		4,300	4,100	4,000	
3.5L EcoBoost® V6	3.73	11,200	4,400	4,300	4,100	3,600	4,200	4,100	3,900	3,300

CARGO VAN

			CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹									
			REAR-WHEEL DRIVE						ALL-WHEEL DRIVE			
Automatic Transmission			150/250/350	150/250/350	350HD	150/250/350	350HD	250/350	350HD	250/350	350HD	350HD DRW
Engine	Axle Ratio	GCWR (lbs.)	130" WB Low Roof	148" WB Low Roof	148" WB Low Roof	148" WB Medium Roof	148" WB Medium Roof	148" WB High Roof	148" WB High Roof	148" WB Extended High Roof	148" WB Extended High Roof	148" WB Extended High Roof
3.5L PFDI V6	3.73	10,800	5,300	5,200		5,000		4,900				
	4.10	12,000	6,400	6,300	6,300	6,100	6,100	6,000	6,000	5,800	5,800	5,600
3.5L EcoBoost V6	3.73	12,600	6,900	6,800	6,800	6,700	6,700	6,600	6,600	6,400		
		13,000									6,700	6,400

			CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT (lbs.) ¹									
			ALL-WHEEL DRIVE									
Automatic Transmission			150/250/350	150/250/350	350HD	150/250/350	350HD	250/350	350HD	250/350	350HD	350HD DRW
Engine	Axle Ratio	GCWR (lbs.)	130" WB Low Roof	148" WB Low Roof	148" WB Low Roof	148" WB Medium Roof	148" WB Medium Roof	148" WB High Roof	148" WB High Roof	148" WB Extended High Roof	148" WB Extended High Roof	148" WB Extended High Roof
3.5L PFDI V6	3.73	10,800	5,100	5,000		4,800		4,700				
	4.10	12,000	6,200	6,100	6,100	5,900	5,900	5,800	5,800	5,600	5,600	5,300
3.5L EcoBoost V6	3.73	12,600	6,700	6,600	6,600	6,500	6,500	6,400	6,400	6,200		
		13,000									6,400	6,200

- Notes:**
- Do not exceed trailer weight of 5,000 lbs. when towing with bumper only.
 - Combined weight of vehicle and trailer cannot exceed listed GCWR.
 - Do not exceed the Maximum Loaded Trailer Weight listed.
 - Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.
 - Transit calculated with SAE J2807® method.

1. Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer. 2. 15-passenger van.



2026 T-350HD Cutaway in Carbonized Gray Metallic

AVAILABLE TRAILER TOWING PACKAGE

Equipment	Transit (53B) ¹	Transit (53D)
4-/7-Pin Connector	I ²	I
Trailer Wiring Harness		I
Trailer Wiring Provision	I	I
Hitch Receiver	I	
Tow/Haul Mode	I	I
Trailer Sway Control		I

LEGEND
I = Equipment is included in the package

Note: Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all vehicles that will be used for towing to help ensure easy, proper connection of trailer lights.

REQUIRED EQUIPMENT

For trailers over 5,000 lbs. – Heavy-Duty Trailer Tow Package (53B)
Your New Vehicle Limited Warranty may be voided if you tow without this.³

Transit[®]

CUTAWAY

Automatic Transmission			CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT (lbs.) ⁴									
Engine	Axle Ratio	GCWR (lbs.)	REAR-WHEEL DRIVE					ALL-WHEEL DRIVE				
			250/350 138" WB	350HD DRW 138" WB	250 156" WB	350HD DRW 156" WB	350HD DRW 178" WB	250/350 138" WB	350HD DRW 138" WB	250 156" WB	350HD DRW 156" WB	350HD DRW 178" WB
3.5L PFDI V6	4.10	12,000	6,500	6,400	6,400	6,200	6,000	6,300	6,100	6,200	6,000	5,700
3.5L EcoBoost [®] V6	3.73	12,600	7,100		6,900			6,800		6,700		
		13,000		7,300		7,100	6,900		7,100		6,900	6,700
		15,000		7,500		7,500	7,500		7,500		7,500	7,500

CHASSIS CAB

Automatic Transmission			CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT (lbs.) ⁴									
Engine	Axle Ratio	GCWR (lbs.)	REAR-WHEEL DRIVE					ALL-WHEEL DRIVE				
			250/350 138" WB	350HD DRW 138" WB	250 156" WB	350HD DRW 156" WB	350HD DRW 178" WB	250/350 138" WB	350HD DRW 138" WB	250 156" WB	350HD DRW 156" WB	350HD DRW 178" WB
3.5L PFDI V6	4.10	12,000	6,500	6,300	6,400	6,200	5,900	6,300	6,100	6,200	6,000	5,700
3.5L EcoBoost V6	3.73	12,600	7,000		6,900			6,800		6,700		
		13,000		7,300		7,100	6,900		7,000		6,900	6,600
		15,000		7,500		7,500	7,500		7,500		7,500	7,500

Notes:

- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found in the vehicle Safety Compliance Certification Label.

FRONTAL AREA LIMITATION

Frontal Area is the total area in square feet that a moving vehicle and trailer exposes to air resistance.

The maximum trailer frontal area that must be considered for a **Transit Van/trailer** combination is **55 sq. ft. for all applications** and for a **Transit Cutaway or Chassis Cab/trailer** combination is **72 sq. ft.* See Incomplete Vehicle Manual (IVM) for frontal area restriction details.** Exceeding these limitations may significantly reduce the performance of your towing vehicle.

*Base vehicle frontal area.

REAR AXLE RATIO CODES

If you do not know the axle ratio of your vehicle, check its Safety Compliance Certification Label (located on the left front door lock facing or the door latch post pillar). Below the bar code, you will see the word AXLE and a two-digit code. Use the chart to find the axle ratio that corresponds to that code.

Rear Axle Ratio	Non-Limited Slip	Limited Slip
3.73	X73	X7L
4.10	Not Available	X4L

FACTORY-INSTALLED TRAILER HITCH RECEIVER OPTION

Included with Trailer Tow Package – Option Code 53B
See Hitch Receiver Weight Capacity chart for the weight-carrying capacity of this hitch receiver. (This capacity also is shown on a label affixed to each receiver.)

HITCH RECEIVER WEIGHT CAPACITY

The maximum weight capacities for the hitch receivers shown below may exceed the maximum loaded trailer weight for the vehicle specified. Refer to the Trailer Towing Selector chart for Maximum Loaded Trailer Weight for this vehicle.

	Weight-Carrying Max. Trailer Capacity (lbs.) ⁵	Max. Tongue Load (lbs.)
Transit Passenger Van	4,500	450
Transit Cargo Van	6,900	690

1. Not available on Cutaway or Chassis Cab models. 2. Includes relay system for backup/B+/running lights. 3. See your Ford Dealer for limited warranty details. 4. Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. For additional information, see your Ford Dealer. 5. Hitch receivers do not include a hitch ball or ball mounting. You are responsible for obtaining the proper hitch ball, ball mounting, and other appropriate equipment to tow both the trailer and its cargo load.

Basic Towing Information

Towing a trailer is demanding on your vehicle, your trailer and your personal driving skills. Follow some basic rules that will help you with your towing experience.

Cargo And Weight Distribution

For optimum handling and braking, the load must be properly distributed

Keep center of gravity low for best handling

Cargo and load capacity limited by weight and weight distribution

Approximately 60% of the allowable cargo weight should be in the front half of the trailer and 40% in the rear (within limits of tongue load or king pin weight)

Load should be balanced from side-to-side to optimize handling and tire wear

Load must be firmly secured to prevent shifting during cornering or braking, which could result in a sudden loss of control

Before Starting

Before setting out on a trip, practice turning, stopping and backing up your trailer in an area away from heavy traffic

Know clearance required for trailer roof

Check equipment (make a checklist)

Backing Up

Back up slowly, with someone spotting near the rear of the trailer to guide you

Place one hand at bottom of steering wheel and move it in the direction you want the trailer to go

Make small steering inputs – slight movement of steering wheel results in much greater movement in rear of trailer

Braking

Allow considerably more distance for stopping with trailer attached

Remember, the braking system of the tow vehicle is rated for operation at the Gross Vehicle Weight Rating (GVWR), not Gross Combination Weight Rating (GCWR)

If your tow vehicle is an F-150®, F-Series Super Duty®, Transit® or Expedition® and your trailer

has electric brakes, the optional Integrated Trailer Brake Controller (TBC) assists in smooth and effective trailer braking by powering the trailer's electric or electric-over-hydraulic brakes with proportional output based on the towing vehicle's brake pressure

If you are experiencing trailer sway and your vehicle is equipped with electric brakes and a brake controller, activate the trailer brakes with the brake controller by hand. Do not apply the tow vehicle brakes as this can result in increased sway¹

Turning

When turning, be sure to swing wide enough to allow trailer to avoid curbs and other obstructions

Towing On Hills

Downshift the transmission to assist braking on steep downgrades and to increase power (reduce lugging) when climbing hills

With TorqShift® transmission, select tow/haul mode to automatically eliminate unwanted gear search when going uphill and help control vehicle speed when going downhill

Parking With A Trailer

Whenever possible, vehicles with trailers should not be parked on a grade. However, if it is necessary, place wheel chocks under the trailer's wheels, following the instructions below

Apply the foot service brakes and hold

Have another person place the wheel chocks under the trailer wheels on the downgrade side

Once the chocks are in place, release brake pedal, making sure the chocks will hold the vehicle and trailer

Apply the parking brake

Shift automatic transmission into park, or manual transmission into reverse

With 4-wheel drive, make sure the transfer case is not in neutral (if applicable)

Starting Out Parked On A Grade

Apply the foot service brake and hold Start the engine with transmission in park (automatic) or neutral (manual)

Shift the transmission into gear and release the parking brake

Release the brake pedal and move the vehicle uphill to free the chocks

Apply the brake pedal while another person retrieves the chocks

Acceleration And Passing

The added weight of the trailer can dramatically decrease the acceleration of the towing vehicle – exercise caution

When passing a slower vehicle, be sure to allow extra distance. Remember, the added length of the trailer must clear the other vehicle before you can pull back in

Signal and make your pass on level terrain with plenty of clearance

If necessary, downshift for improved acceleration

Driving With An Automatic Overdrive Transmission

With certain automatic overdrive transmissions, towing – especially in hilly areas – may cause excessive shifting between overdrive and the next lower gear

When available, select tow/haul mode to automatically eliminate unwanted gear search and help control vehicle speed when going downhill

Driving With Cruise Control²

Turn off the cruise control with heavy loads or in hilly terrain. The cruise control may turn off automatically when you are towing on long, steep grades. Use caution while driving on wet roads and avoid using cruise control in rainy or winter weather conditions

Tire Pressure

Underinflated tires get hot and may fail, leading to possible loss of vehicle control

Overinflated tires may wear unevenly and compromise traction and stopping capability

Tires should be checked often for conformance to recommended cold inflation pressures

Spare Tire Use

A conventional, identical full-size spare tire is required for trailer towing (mini, compact and dissimilar full-size spare tires should not be used; always replace the spare tire with a new road tire as soon as possible)

On The Road

After about 50 miles, stop in a protected location and double-check:

Trailer hitch attachment

Lights and electrical connections

Trailer wheel lug nuts for tightness

Engine oil – check regularly throughout your trip

High Altitude Operation

Your vehicle may have reduced performance when operating at high altitudes and when heavily loaded or towing a trailer. While driving at elevation, in order to match driving performance as perceived at sea level, reduce Gross Vehicle Weight (GVW) and Gross Combination Weight (GCW) by 2% per 1,000 ft. elevation

Powertrain/Frontal Area Considerations

The charts in this Guide show the minimum powertrain needed to achieve an acceptable towing performance for the listed GCW of tow vehicle and trailer

Under certain conditions, however, (e.g., when the trailer has a large frontal area that adds substantial air drag or when trailering in hilly or mountainous terrain) it is wise to choose a vehicle with a higher rating

Towing performance is maximized with a low-drag, rounded front design trailer

Selecting A Trim Series

Your specific vehicle's tow capability could be reduced based on weight of selected trim series and option content

Note: For additional trailering information pertaining to your vehicle, refer to the vehicle Owner's Manual.

1. Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. Remember that even advanced technology cannot overcome the laws of physics. It's always possible to lose control of a vehicle due to inappropriate driver input for the conditions. 2. Driver-assist features are supplemental and do not replace the driver's attention, judgment and need to control the vehicle. They do not make your vehicle autonomous or replace your responsibility to drive safely. Please only use if you will pay attention to the road and be prepared to take over at any time. See Owner's Manual for details and limitations.